



HIDRAGRUP

Powered by passion



PRESSES

50 TN PRESS (HYDRAULIC).

Main Characteristics.

Dimensions (mm).	2350x2450x5400
Working area (mm) - starting from.	1500x1200.
Distance between lower & upper plates (mm).	1700.
Max upper tool weight (Kg).	4000.
Max. lower tool weight (Kg).	5000.
Columns (mm).	Ø120.
Rear door.	Roller type.
Lateral protections.	Plexiglass sheets.
Service Platform.	On top.
Manometers.	Checkin zero pressure.
Ladder.	Left / Right.

Hydraulic equipment.

Location.	Upper platform.
Tubes.	Rigid.
Cylinder stroke (mm).	1000 mm.
Cylinder pressure (kN).	1 x 500.
Dynamic Speed control.	Yes.
Pressure control.	Yes.
Safety system.	Antifall system.

Electrical installation Electrical cabinet with all required protection elements. PLC SIEMENS with 48 outpus & 56 inputs . Operators control panel integrates buttons and a HMI 7.

Communications

Profinet.	Standard.
Profibus.	Optional.
Profisafe.	Optional.

Optional items	Linear/Rotary tool change system.	Side channel blower.
	Integrated IR oven.	Hydraulic tool clamping (automatic).
	Hydraulic lines to plates for tool services.	Robotic arms.
	Vacuum pump.	